

# Installing a Toilet

1. Adjective
2. Noun
3. Adjective
4. Noun
5. Noun
6. Verb - Base Form
7. Noun
8. Adjective
9. Noun

# Installing a Toilet

Insert the long \_\_\_\_\_ Adjective closet bolts, threaded-end up, into the flange collar's slots. Slip a brass \_\_\_\_\_ Noun over each.

Gently press a \_\_\_\_\_ Adjective \_\_\_\_\_ Noun, flat-side down, over the flange.

Lift the toilet bowl over the flange, align the holes in its base with the closet bolts, and lower the base onto the \_\_\_\_\_ Repeat Last Noun.

Without twisting or rocking, press the bowl down onto the \_\_\_\_\_ Repeat Last Adjective \_\_\_\_\_ Repeat Last Noun until the bowl's base rests on the floor. If the floor is uneven, shim the bowl with a stainless steel \_\_\_\_\_ Noun.

Slip a nylon washer over each bolt, then \_\_\_\_\_ Verb - Base Form the nuts. \_\_\_\_\_ Repeat Last Verb - Base Form the nuts with a \_\_\_\_\_ Noun one quarter turn at a time, alternating between the two. Stop when the \_\_\_\_\_ Repeat Last Noun meets firm resistance; overtightening will crack the bowl.

With a hacksaw, trim the closet bolts at a point two threads above the top of the nut. Snap a \_\_\_\_\_ Adjective \_\_\_\_\_ Noun into place.

