

# Winterize your Boat

1. Adjective
2. Plural Noun
3. Noun
4. Adjective
5. Noun
6. Plural Noun
7. Verb
8. Plural Noun
9. Noun
10. Adjective
11. Adjective
12. Noun
13. Noun
14. Number
15. Plural Noun
16. Verb
17. Adjective
18. Plural Noun

# Winterize your Boat

1. According to the instructions on the bottle, pour the correct amount of \_\_\_\_\_ Adjective \_\_\_\_\_ Plural noun into the boat gas tank.

2. Have antifreeze handy and open the \_\_\_\_\_ Noun intake on your boat that allows you to connect an external \_\_\_\_\_ Adjective \_\_\_\_\_ Noun.

3. Start the boat motor and pour 1/2 gallon the of the antifreeze into the water intake. This will clear out any \_\_\_\_\_ Plural noun that may be left in the motor from your last use, and will also allow the fuel stabilizer to \_\_\_\_\_ Verb \_\_\_\_\_ Plural noun in the gas tank.

4. Stop the boat motor.

5. Use the remaining antifreeze to pour liberally throughout the engine compartment and any other areas of the boat that may have water in them and be at risk of cracking from frozen \_\_\_\_\_ Noun expansion.

6. Remove the \_\_\_\_\_ Adjective wires from the battery terminals, then remove the battery from the boat.

7. Place the battery in a heated area such as your \_\_\_\_\_ Adjective \_\_\_\_\_ Noun for the winter.

8. Remove all spark plug/ignition wires from the spark plugs, then remove all           Noun           plugs from the engine cylinders.

9. Place 1 or           Number           drops of oil into the cylinders through the spark plug holes. From what I hear, this can actually prevent small amounts of oxidation by allowing the oil to collect           Plural noun           that may develop in the cylinders.

10. Put the spark plugs back in the cylinders, but           Verb           the           Adjective                     Plural noun          .